



IN THE CLAIMS

Please amend claims 35, 42 and 49, as set forth below.

The pending claims, along with their current status and amendments, if any, are set forth below:

**RECEIVED**

JUL 15 2003

Technology Center 2600

Sub HI  
1-34. (Previously canceled).

35. (Currently Amended) A color display system, comprising:

a color display device that stores color correction data corresponding to an input-output color characteristic associated with the color display device, the color correction data being chosen to allow the display device to display color uniformly according to a given color standard; and

a computer system that is adapted to:

load the color correction data from the color display device; and  
create a video signal based on the color correction data.

36. (Original) The color display system set forth in claim 35, wherein the computer system is adapted to send the video signal to the color display device.

37. (Original) The color display system set forth in claim 35, wherein the color correction data comprises a plurality of equation coefficients that represent the input-output color characteristic associated with the color display device.

38. (Original) The color display system set forth in claim 35, wherein the color correction data comprises a plurality of coefficients that represent a signal input-to-first color output relationship of the color display device.

39. (Original) The color display system set forth in claim 38, wherein the coefficients are for a polynomial equation.

40. (Original) The color display system set forth in claim 38, wherein the plurality of coefficients can be utilized in a third order polynomial equation which predicts the brightness of the first color to within 0.3 foot-lamberts for each input signal for the color display device.

41. (Original) The color display system set forth in claim 35 wherein the color display device can be at least one of a VGA monitor, a MultiSync monitor, a flat panel NCD display, a flat panel SPU display, a flat panel LCD display, a reflective LCD display, and a FED display device.

42. (Original) A color display device, comprising:  
a display screen for displaying a color image; and  
a memory device that is adapted to store color correction data corresponding to an input-output color characteristic associated with the display screen, the color correction data being chosen to allow the color display device to display color uniformly according to a given color standard, the color correction data being adapted to be loaded into a computer system associated with the color display device for use by the computer system in creating a video signal based on the color correction data.

43. (Original) The color display device set forth in claim 42, wherein the color display device is adapted to receive the video signal from the computer system.

44. (Original) The color display device set forth in claim 42, wherein the color correction data comprises a plurality of equation coefficients that represent the input-output color characteristic associated with the color display device.

45. (Original) The color display device set forth in claim 42, wherein the color correction data comprises a plurality of coefficients that represent a signal input-to-first color output relationship of the color display device.

46. (Original) The color display device set forth in claim 45, wherein the coefficients are for a polynomial equation.

47. (Original) The color display device set forth in claim 45, wherein the plurality of coefficients can be utilized in a third order polynomial equation which predicts the brightness of the first color to within 0.3 foot-lamberts for each input signal for the color display device.

48. (Original) The color display system set forth in claim 42 wherein the color display device can be at least one of a VGA monitor, a MultiSync monitor, a flat panel NCD display, a flat panel SPU display, a flat panel LCD display, a reflective LCD display, and a FED display device.

49. (Original) A method of providing color correction in a color display system, the color display system comprising a color display device that stores color correction data corresponding to an input-output color characteristic associated with the color display device, the color correction data being chosen to allow the display device to display color uniformly according to a given color standard, and a computer system that is adapted to provide a video signal to the color display device, the method comprising:

retrieving the color correction data from the color display device;  
using the color correction data to create the video signal.

61  
could  
50. (Original) The method set forth in claim 49, comprising delivering the video signal to the color display device.

51. (Original) The method set forth in claim 49, comprising predicting the brightness of a first color to within 0.3 foot-lamberts for at least one input signal to the color display device.